## Annex I International procurement (UN-Habitat) DP XII

DP XII			
Code No.	Item Description	Unit	Qty
09-01-00001	Ordinary Portland Cement		
09-01-00002	Mild steel reinforcement bars, twisted (deformed) and commercial grade, yield strength 60 ksi ,length 6m ,different sizes.		
09-01-00003	Steel plate (flat) gauge 20,size 4'x8', different sizes		
09-01-00004	Galvanized steel plate (flat) gauge 18,size 4'x8'		
09-01-00005	Standard mild steel ,T profile , 6m length,25x25x3 mm		
09-01-00006	Standard mild stool 7 profile Cm length 25v25v2mm		
	Standard mild steel ,Z profile , 6m length,25x25x3mm Standard mild square steel bars 10x10mm ,6m length		
09-01-00007	Standard mild square steer bars Tox Tomm, om length		
09-01-00008	Standard mild steel square pipes (hollow) 40x40x3 mm , 6m length		
09-01-00009	mild steel weld hot dip galvanized iron pipe for drinking water supply confirming to ISO R65-1981, medium series standards. Threaded BS21 (ISO R7) with standard socket at one end and plastic heavy gauge cap protection at the other end, 6 meter length, different diameters. With fittings		
09-01-00010	Ductile iron pipe with rubber gasket joints, Tyton joints 6m length abd PN20-PN25, with fittings different diameters.		
09-01-00011	Submersible pump type GRUDFOS, 3x3BD, 380/415V, 50hz and motorable, with cable termination kit, 4 cable clip, 170m length of drop cable 3x16cm and control panel: Different types as below:		
09-01-00012	Turbine Submersible pump with vertical motor +gear box + discharge +pipes colman bearing with shaft:10m3/hr, H=160m ,pipe 3 m.l, Dia.3" or 4" with shaft for depth of 120m.		
09-01-00013	Booster centrifugal pump to be used for pumping drinking water, coupled with electrical driven motor with star delta connection and control panel V=380V, 50Hz, three phase with fittings (Valves, Non-return valves with strainer steel flanges, steel elbow, bolts, nuts and gaskets), maximum 25 bar with parts for two year operation.		
09-01-00014	Generator: The engine is PERKINS-UK, 1500 RPM, diesel fuel with a water radiator for cooling. 3 phase, 380V-415V, 50Hz. For continuous use, altitude 700m, with AMF(Automatic main failure),indoor, average humidity, 50 degrees centigrade, different sizes,		
09-01-00015	Galvanised steel casing pipe for deep wells 6 m length, different sizes		
09-01-00016	Galvanized slotted steel casing pipe for deep wells 6 m length, different sizes		
09-01-00017	Compact units for water treatment , Different sizes		
09-01-00018	Elevated Steel water tanks on stages		
09-01-00019	Survey equipment		
09-01-00020	Road safety equipment		
09-01-00021	Road sfaty materials, signs, barriers		
09-01-00022	Small size mixers		
09-01-00023	Different kind of equipment for Solid waste		
09-01-00024	Vibratos, compactors		
09-01-00025	Fire Fighting Equipment		
09-01-00026	Concrete block production units		
09-01-00027	Tools for Bridge maintenance		
09-01-00028	Spare parts for Equipment		
09-01-00029	Plotters, Total stations, Destomats		