

Annex I
International procurement (UN-Habitat)
DP XII

| Code No. | Item Description | Unit | Qty |
|-------------|---|------|---------|
| 09-01-00001 | Ordinary Portland Cement | MT | 200,000 |
| 09-01-00002 | Mild steel reinforcement bars, twisted (deformed) and commercial grade, yield strength 60 ksi ,length 6m ,different sizes. | MT | 25,000 |
| 09-01-00003 | Steel plate (flat) gauge 20,size 4'x8', different sizes | MT | 10 |
| 09-01-00004 | Galvanized steel plate (flat) gauge 18,size 4'x8' | MT | 20 |
| 09-01-00005 | Standard mild steel ,T profile , 6m length,25x25x3 mm | MT | 10 |
| 09-01-00006 | Standard mild steel ,Z profile , 6m length,25x25x3mm | MT | 10 |
| 09-01-00007 | Standard mild square steel bars 10x10mm ,6m length | MT | 15 |
| 09-01-00008 | Standard mild steel square pipes (hollow) 40x40x3 mm , 6m length | No. | 25 |
| 09-01-00009 | mild steel weld hot dip galvanized iron pipe for drinking water supply confirming to ISO R65-1981 , medium series standards. Threaded BS21 (ISO R7) with standard socket at one end and plastic heavy gauge cap protection at the other end, 6 meter length, different diameters.With fittings | No. | 2,000 |
| 09-01-00010 | Ductile iron pipe with rubber gasket joints, Tyton joints 6m length abd PN20-PN25 ,with fittings different diameters. | No. | 20,000 |
| 09-01-00011 | Submersible pump type GRUDFOS, 3x3BD, 380/415V, 50hz and motorable , with cable termination kit, 4 cable clip, 170m length of drop cable 3x16cm and control panel : Different types as below: | No. | 50 |
| 09-01-00012 | Turbine Submersible pump with vertical motor +gear box + discharge +pipes colman bearing with shaft:10m3/hr, H=160m ,pipe 3 m.l, Dia.3" or 4" with shaft for depth of 120m. | No. | 30 |
| 09-01-00013 | Booster centrifugal pump to be used for pumping drinking water, coupled with electrical driven motor with star delta connection and control panel V=380V, 50Hz, three phase with fittings (Valves, Non-return valves with strainer steel flanges, steel elbow, bolts, nuts and gaskets...), maximum 25 bar with parts for two year operation. | No. | 15 |
| 09-01-00014 | Generator: The engine is PERKINS-UK, 1500 RPM, diesel fuel with a water radiator for cooling. 3 phase, 380V-415V, 50Hz. For continuous use , altitude 700m , with AMF(Automatic main failure),indoor, average humidity, 50 degrees centigrade , different sizes, | No. | 40 |
| 09-01-00015 | Galvanised steel casing pipe for deep wells 6 m length , different sizes | No. | 300 |
| 09-01-00016 | Galvanized slotted steel casing pipe for deep wells 6 m length, different sizes | No. | 250 |
| 09-01-00017 | Compact units for water treatment , Different sizes | No. | 4 |
| 09-01-00018 | Elevated Steel water tanks on stages | No. | 9 |
| 09-01-00019 | Survey equipment | No. | 200 |
| 09-01-00020 | Road safety equipment | No. | 30 |
| 09-01-00021 | Road sfaty materials, signs, barriers | Lot. | 3 |
| 09-01-00022 | Small size mixers | No. | 60 |
| 09-01-00023 | Different kind of equipment for Solid waste | No. | 30 |
| 09-01-00024 | Vibratos, compactors | No. | 200 |
| 09-01-00025 | Fire Fighting Equipment | No. | 25 |
| 09-01-00026 | Concrete block production units | No. | 3 |
| 09-01-00027 | Tools for Bridge maintenance | No. | 20 |
| 09-01-00028 | Spare parts for Equipment | Lot | 3 |
| 09-01-00029 | Plotters, Total stations, Destomats | No. | 20 |